

Silverton 34c
Frame

<u>Part of boat:</u>	<u>P/N</u>	
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 1	<i>4 Bow frame</i>	
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 2	<i>QR Bimini hinge (teardrop)</i>	401
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 2	<i>QP Angle deck mount</i>	SSF320-1
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 2	<i>Rail mount</i>	SSF366
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 4	<i>10/24x1 1/2" mach. Bolts and nuts</i>	PP466150
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 8	<i>Fender washers</i>	FW25100
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 8	<i>#10/24x3/4" mach. Bolts and nuts</i>	PP4166075
	WITH ARCH ADD;	
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 2	<i>QR Bimini hinge w/o pin</i>	401-B
<hr style="width: 100px; display: inline-block; vertical-align: middle; margin-right: 10px;"/> 4	<i>#10 x 3/4in Oval head Screw</i>	OP10075

Silverton 34c
Frame



The center line of the main mount is 2" down from the top edge inside the bridge.



Place the pivot point of the QR bimini hinge 3" back from the point shown in this picture. Secure mount with 10x24 nuts, bolts and washers provided. Repeat on the opposite side.

Silverton 34c
Frame



A second mount is provided for boats with a radar arch. Measure forward 12" and secure in place. These mounts are for when the bimini is in the boot only. Repeat on the opposite side.



Measure forward from the same point on the bridge 48" to the center of the QP angle deck mount.

Silverton 34c
Frame



Secure the mount so that it runs parallel with the center line of the boat. Use #10x3/4 screws provided. Repeat on the opposite side.



Measure back from the same point on the bridge to the rail and mark 56". Secure the rail mount on center with the 10x24 nuts, bolts and washers provided. Angle the mounts in about a 1/2" to allow the strut to taper in to the frame. Repeat on the opposite side.

Silverton 34c
Frame



Place the frame in the mounts with the longer struts forward. Zip the bimini top to the frame with the Gioia Sails labels on the two forward bows.